

Information sheet (Lot.10)

This information includes the results of calculation of the seasonal energy consumption and efficiency for air conditioner in regards to ErP pursuant to the Commission Regulation(EU) No.206/2012 and No.626/2011.

Information to identify the model(s) to which the information relates to:

AIR CONDITIONER
 TYPE : MULTI SPLIT
 WALL MOUNTED
 Indoor unit(s) : ASEH07KMCG x 1 + ASEH09KMCG x 2
 Outdoor unit : AOEG24KBCA3
 BRAND : FUJITSU

N/A = Not Applicable

Function			
Cooling	Yes	Average	Yes
Heating	Yes	Warmer	No
		Colder	No

Design load				Seasonal efficiency			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Cooling	Pdesignc	6.8	kW	Cooling	SEER	8.50	-
Heating/Average	Pdesignh	6.0	kW	Heating/Average	SCOP/A	4.60	-
Heating/Warmer	Pdesignh	N/A	kW	Heating/Warmer	SCOP/W	N/A	-
Heating/Colder	Pdesignh	N/A	kW	Heating/Colder	SCOP/C	N/A	-

Cooling							
Declared capacity for cooling, at indoor temperature 27 (19) °C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27 (19) °C and outdoor temperature Tj			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = 35°C	Pdc	6.80	kW	Tj = 35°C	EER d	3.90	-
Tj = 30°C	Pdc	5.01	kW	Tj = 30°C	EER d	6.05	-
Tj = 25°C	Pdc	3.22	kW	Tj = 25°C	EER d	10.51	-
Tj = 20°C	Pdc	2.84	kW	Tj = 20°C	EER d	16.79	-

Heating/Average							
Declared capacity for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance/Average season, at indoor temperature 20 °C and outdoor temperature Tj			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = -7°C	Pdh	5.31	kW	Tj = -7°C	COPd	2.80	-
Tj = 2°C	Pdh	3.23	kW	Tj = 2°C	COPd	4.67	-
Tj = 7°C	Pdh	3.06	kW	Tj = 7°C	COPd	6.30	-
Tj = 12°C	Pdh	2.84	kW	Tj = 12°C	COPd	8.05	-
Tj = bivalent temperature	Pdh	5.31	kW	Tj = bivalent temperature	COPd	2.80	-
Tj = operating limit*	Pdh	5.10	kW	Tj = operating limit*	COPd	2.77	-

Heating/Warmer							
Declared capacity for heating/Warmer season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance/Warmer season, at indoor temperature 20 °C and outdoor temperature Tj			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = 2°C	Pdh	N/A	kW	Tj = 2°C	COPd	N/A	-
Tj = 7°C	Pdh	N/A	kW	Tj = 7°C	COPd	N/A	-
Tj = 12°C	Pdh	N/A	kW	Tj = 12°C	COPd	N/A	-
Tj = bivalent temperature	Pdh	N/A	kW	Tj = bivalent temperature	COPd	N/A	-
Tj = operating limit*	Pdh	N/A	kW	Tj = operating limit*	COPd	N/A	-

Heating/Colder							
Declared capacity for heating/Colder season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance/Colder season, at indoor temperature 20 °C and outdoor temperature Tj			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = -7°C	Pdh	N/A	kW	Tj = -7°C	COPd	N/A	-
Tj = 2°C	Pdh	N/A	kW	Tj = 2°C	COPd	N/A	-
Tj = 7°C	Pdh	N/A	kW	Tj = 7°C	COP d	N/A	-
Tj = 12°C	Pdh	N/A	kW	Tj = 12°C	COP d	N/A	-
Tj = bivalent temperature	Pdh	N/A	kW	Tj = bivalent temperature	COP d	N/A	-
Tj = operating limit*	Pdh	N/A	kW	Tj = operating limit*	COP d	N/A	-
Tj=-15°C	Pdh	N/A	kW	Tj = -15°C	COP d	N/A	-

Bivalent temperature				Operating limit temperature			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heating/Average	Tbiv	-7	°C	Heating/Average	Tol	-15	°C
Heating/Warmer	Tbiv	N/A	°C	Heating/Warmer	Tol	N/A	°C
Heating/Colder	Tbiv	N/A	°C	Heating/Colder	Tol	N/A	°C

Cycling interval capacity				Cycling interval efficiency			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
For cooling	Pcycc	N/A	kW	For cooling	EERcyc	N/A	-
For heating	Pcyh	N/A	kW	For heating	COPcyc	N/A	-
Degradation coefficient cooling	Cdc	0.25	-	Degradation coefficient heating	Cdh	0.25	-

Electric power input in power modes other than 'active mode'				Annual electricity consumption			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Off mode (Cooling/Heating)	P _{OFF}	3.0/3.0	W	Cooling	Q _{CE}	280	kWh/a
Standby mode (Cooling/Heating)	P _{SB}	3.0/3.0	W	Heating/Average	Q _{HE}	1826	kWh/a
Thermostat-off mode (Cooling/Heating)	P _{TO}	7.0/15.0	W	Heating/Warmer	Q _{HE}	N/A	kWh/a
Crankcase heater mode (Cooling/Heating)	P _{CK}	0.0/0.0	W	Heating/Colder	Q _{HE}	N/A	kWh/a

Capacity control		Other items		
Item	Y/N	Item	Symbol	Value Unit
Fixed	No	Sound power level (Indoor/Outdoor)	L _{WA}	55.0/61.0 dB(A)
Staged	No	Global warming potential	GWP	675 kgCO ₂ eq.
Variable	Yes	Rated air flow (Indoor/Outdoor)	-	700/2270 m ³ /h

Contact details for obtaining more information	GENERAL Inc. 3-3-17, Suenaga, Takatsu-ku, Kawasaki, 213-8502, Japan
--	--

*: Temperature at part load E condition(EN 14825)

V20121214

Information of indoor unit combination

Indoor unit combination (Wall-mounted type KM/KG/KE series only)

N/A = Not Applicable

Combination of Indoor unit *1			Cooling				Heating/Average				Heating/Warmer				Heating/Colder			
room1	room2	room3	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class
			Pdesignhc kW	SEER	QcE kWh/a	-	Pdesignh kW	SCOP/A	QcE kWh/a	-	Pdesignh kW	SCOPW	QcE kWh/a	-	Pdesignh kW	SCOP/C	QcE kWh/a	-
07	07	-	4.0	8.3	169	A++	4.0	4.2	1333	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	-	4.5	8.2	192	A++	4.0	4.2	1333	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	-	5.5	8.0	241	A++	5.0	4.0	1750	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	14	-	6.0	7.6	276	A++	5.4	4.0	1890	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	18	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	-	5.0	8.1	216	A++	4.5	4.1	1537	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	-	6.0	7.6	276	A++	5.4	4.0	1890	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	14	-	6.5	7.2	316	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	18	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	12	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	14	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	18	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14	14	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14	18	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	07	6.0	8.6	244	A+++	5.4	4.7	1609	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	09	6.5	8.5	268	A+++	5.8	4.6	1765	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	18	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	09	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	18	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	14	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	09	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	18	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	14	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	12	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

*1
07 = 7000Btu/h class = 2.0kW class
09 = 9000Btu/h class = 2.5kW class
12 = 12000Btu/h class = 3.5kW class
14 = 14000Btu/h class = 4.0kW class
18 = 18000Btu/h class = 5.0kW class

Indoor unit combination (Wall-mounted type KM/KG/KE series including KJ series only)

N/A = Not Applicable

Combination of Indoor unit *1				Cooling				Heating/Average				Heating/Warmer				Heating/Colder			
room1	room2	room3	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	
			Pdesign _{cl}	SEER	Q _{cl} E	-	Pdesign _{cl}	SCOP/A	Q _{cl} E	-	Pdesign _{cl}	SCOP/W	Q _{cl} E	-	Pdesign _{cl}	SCOP/C	Q _{cl} E	-	
			kW	-	kWh/a	-	kW	-	kWh/a	-	kW	-	kWh/a	-	kW	-	kWh/a	-	
05	09	-	4.0	8.2	171	A++	4.0	4.2	1332	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	12	-	5.0	8.1	216	A++	4.5	4.1	1535	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	14	-	5.5	7.7	250	A++	5.0	4.0	1750	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	18	-	6.5	7.2	316	A++	5.8	4.0	2030	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	07	-	4.0	8.2	171	A++	4.0	4.2	1332	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	09	-	4.5	8.2	192	A++	4.0	4.2	1332	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	12	-	5.5	8.0	241	A++	5.0	4.0	1750	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	14	-	6.0	7.6	276	A++	5.4	4.0	1889	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	18	-	6.8	6.9	345	A++	5.8	4.0	2030	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	09	-	5.0	8.1	216	A++	4.5	4.1	1535	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	12	-	6.0	7.6	276	A++	5.4	4.0	1889	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	14	-	6.5	7.2	316	A++	5.8	4.0	2030	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	18	-	6.8	6.9	345	A++	5.8	4.0	2030	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
12	12	-	6.8	6.9	345	A++	5.8	4.0	2030	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
12	14	-	6.8	6.9	345	A++	5.8	4.0	2030	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
12	18	-	6.8	6.9	345	A++	5.8	4.0	2030	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
14	14	-	6.8	6.9	345	A++	5.8	4.0	2030	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
14	18	-	6.8	6.9	345	A++	5.8	4.0	2030	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	05	05	4.5	8.5	185	A+++	4.0	4.6	1217	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	05	07	5.0	8.5	206	A+++	4.5	4.6	1369	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	05	09	5.5	8.5	226	A+++	5.0	4.5	1553	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	05	12	6.5	8.5	268	A+++	5.8	4.5	1803	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	05	14	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	05	18	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	07	07	5.5	8.5	226	A+++	5.0	4.5	1553	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	07	09	6.0	8.5	247	A+++	5.4	4.6	1643	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	07	12	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	07	14	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	07	18	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	09	09	6.5	8.5	268	A+++	5.8	4.5	1803	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	09	12	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	09	14	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	09	18	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	12	12	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	12	14	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	12	18	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
05	14	14	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	07	07	6.0	8.5	247	A+++	5.4	4.6	1643	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	07	09	6.5	8.5	268	A+++	5.8	4.5	1803	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	07	12	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	07	14	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	07	18	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	09	09	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	09	12	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	09	14	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	09	18	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	12	12	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	12	14	6.8	8.5	280	A+++	6.0	4.6	1825	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
07	14	14	6.8	8.5	280	A+++	6.0	4.6	1825	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	09	09	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	09	12	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	09	14	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	09	18	6.8	8.4	283	A++	6.0	4.5	1867	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	12	12	6.8	8.5	280	A+++	6.0	4.6	1825	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
09	12	14	6.8	8.5	280	A+++	6.0	4.6	1825	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
12	12	12	6.8	8.5	280	A+++	6.0	4.6	1825	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	

*1

05 = 5000Btu/h class = 1.5kW class

07 = 7000Btu/h class = 2.0kW class

09 = 9000Btu/h class = 2.5kW class

12 = 12000Btu/h class = 3.5kW class

14 = 14000Btu/h class = 4.0kW class

18 = 18000Btu/h class = 5.0kW class

Indoor unit combinations (excluding combinations consisting only of wall-mounted units of the KM, KG, and KE series, including KJ series)

N/A = Not Applicable

Combination of Indoor unit *1			Cooling				Heating/Average				Heating/Warmer				Heating/Colder			
room1	room2	room3	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class
			Pdesign _{gnc}	SEER	Q _{gE}		Pdesign _{gh}	SCOP/A	Q _{gE}		Pdesign _{gh}	SCOPW	Q _{gE}		Pdesign _{gh}	SCOP/C	Q _{gE}	
			kW	-	kWh/a	-	kW	-	kWh/a	-	kW	-	kWh/a	-	kW	-	kWh/a	-
05	09	-	4.0	6.7	209	A++	4.0	4.0	1400	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	12	-	5.0	6.5	269	A++	4.5	3.9	1615	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	14	-	5.5	6.4	301	A++	5.0	3.8	1842	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	18	-	6.5	5.5	414	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	-	4.0	6.7	209	A++	4.0	4.0	1400	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	-	4.5	6.6	239	A++	4.0	4.0	1400	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	-	5.5	6.4	301	A++	5.0	3.8	1842	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	14	-	6.0	6.0	350	A+	5.4	3.8	1989	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	18	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	-	5.0	6.5	269	A++	4.5	3.9	1615	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	-	6.0	6.0	350	A+	5.4	3.8	1989	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	14	-	6.5	5.5	414	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	18	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	12	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	14	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	18	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14	14	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14	18	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	05	4.5	6.6	239	A++	4.0	4.2	1333	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	07	5.0	6.5	269	A++	4.5	4.1	1537	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	09	5.5	6.4	301	A++	5.0	4.1	1707	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	12	6.5	6.2	367	A++	5.8	3.9	2082	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	14	6.8	6.2	387	A++	5.9	3.9	2127	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	07	5.5	6.4	301	A++	5.0	4.1	1707	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	09	6.0	6.3	333	A++	5.4	4.0	1890	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	12	6.8	6.2	387	A++	6.0	3.9	2182	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	09	09	6.5	6.2	367	A++	5.8	3.9	2082	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	09	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	09	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	09	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	12	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	12	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	12	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	14	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	07	6.0	6.3	333	A++	5.4	4.0	1890	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	09	6.5	6.2	367	A++	5.8	3.9	2082	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	09	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	09	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	12	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

*1

05 = 5000Btu/h class = 1.5kW class

07 = 7000Btu/h class = 2.0kW class

09 = 9000Btu/h class = 2.5kW class

12 = 12000Btu/h class = 3.5kW class

14 = 14000Btu/h class = 4.0kW class

18 = 18000Btu/h class = 5.0kW class

Information of unit specification

Model Type	Model No.	Capacity Class	Dimension [H x W xD]	Sound power level(Cooling)	Sound power level(Heating)
		kW	mm	dB(A)	dB(A)
OUTDOOR	AOEG24KBCA3	-	716 x 820 x 315	61	67
WALL MOUNTED	ASEH05KJCAL ASEH05KJCALB	1.5	270 x 798 x 240	50	50
	ASEH07KJCAL ASEH07KJCALB	2.0		51	51
	ASEH09KJCAL ASEH09KJCALB	2.5		55	56
	ASEH12KJCAL ASEH12KJCALB	3.5		56	56
	ASEH14KJCAL ASEH14KJCALB	4.0		59	59
	ASEH05KNCA ASEH07KNCA ASEH09KNCA ASEH12KNCA	1.5 2.0 2.5 3.5	270 x 784 x 222	50 51 56 57	50 51 56 57
	ASYG07KMCF ASEH07KMCG ASEH07KMCG-B	2.0		54	56
	ASYG09KMCF ASEH09KMCG ASEH09KMCG-B	2.5		55	57
	ASYG12KMCF ASEH12KMCG ASEH12KMCG-B	3.5		55	58
	ASYG14KMCF ASEH14KMCG ASEH14KMCG-B	4.0		57	59
	ASYG07KGTG ASEH07KGTG ASYG09KGTG ASEH09KGTG ASYG12KGTG ASEH12KGTG ASYG14KGTG ASEH14KGTG	2.0 2.5 3.5 4.0	270 x 834 x 215	54 55 56 57	56 57 58 59
	ASYG18KMTE ASEG18KMTE ASEH18KMTGL	5.0		60	61
	ASYG07KETF ASEG07KETF ASYG07KETF-B ASEG07KETF-B	2.0	295 x 950 x 230	54	56
	ASYG09KETF ASEG09KETF ASYG09KETF-B ASEG09KETF-B	2.5		55	57
	ASYG12KETF ASEG12KETF ASYG12KETF-B ASEG12KETF-B	3.5		55	58
	ASYG14KETF ASEG14KETF ASYG14KETF-B ASEG14KETFB	4.0		57	59
CASSETTE	AUXG07KVLA AUXG09KVLA AUXG12KVLA AUXG14KVLA AUXG18KVLA	2.0 2.5 3.5 4.0 5.0	245 x 570 x 570 (Panel: 49 x 620 x 620)	46 46 49 50 50	47 47 49 55 55
	ARXG07KSLAP ARXG09KSLAP ARXG12KSLAP ARXG14KSLAP ARXG18KSLAP	2.0 2.5 3.5 4.0 5.0		52 54 55 60 58	53 56 57 62 59
	ARXG07KLLAP ARXG09KLLAP ARXG12KLLAP ARXG14KLLAP ARXG18KLLAP	2.0 2.5 3.5 4.0 5.0	198 x 700 x 620	57 57 58 60	57 57 58 60
	ARXG18KLLAP	5.0		58	58
	ARXH12KMTAP ARXH14KMTAP ARXH18KMTAP	3.5 4.0 5.0	240 x 700 x 700	58 59 60	58 59 60
FLOOR	AGYG09KVCA AGEG09KVCA AGEH09KVCCCL	2.5	600 x 740 x 200	52	52
	AGYG12KVCA AGEG12KVCA AGEH12KVCCCL	3.5		55	55
	AGYG14KVCA AGEG14KVCA AGEH14KVCCCL	4.0		56	56
CEILING	ABYG18KRTA ABEG18KRTA	5.0	235 x 1080 x 705	53	53